# DiskOnModule Standard DG & DG Wide Temp Series



Rev. A.2 July 2006

### **Table of Contents**

1. Description	1
2. Features	1
3. Introduction	1
4. Specification	2
5. Physical Outline	4



**Revision History** 

Revision	Date	History	Remark
A.0	01/26 '05	First document announced	
A.1	08/30 '05	Correct Spec data	
A.2	07/11 '06	Modify the format	

"PQI reserves the right to make changes without notification when fit, form, function, quality and reliability are not affected. The data sheets do not constitute contract documents and should not be considered part of the specification for purposes of any warranty."

Rev. A.2 July 2006



#### 1. Description

PQI's **DiskOnModule DG series** based on NAND flash memory controller technology. This product complies with 44 PIN IDE (ATA) standard interface and is suitable for data storage memory medium for portable system. By using **DiskOnModule** it is possible to operate good performance for the portable system, which have IDE interface slots

#### 2. Features

- High Performance
- Non-volatile Flash Memory
   The DOM is implemented by using NAND type flash memory, which is a high density, non-volatile read/write device. Flash data retention is guaranteed for at least 10 years, with no battery or other power source required.
- 100% True Mode IDE HDD Compatible
- Broad Operating System and Processors Supports
- Capacities 32MB~2GB
- Low Power Consumption
- Robust Error Correction
- High Reliability

#### 3. Introduction

#### 1.About This Manual

This manual provides instructions for the installation and specification of PQI's *DiskOnModule*; *DiskOnModule* is designed for use in PCs, and their respective compatible computers.

#### 2.What is DiskOnModule?

PQI's DiskOnModule is a storage device based on flash memory technology, which emulates an ordinary magnetic hard disk. The DiskOnModule series products provide an all in one module solution for solid-state flash disk. The DiskOnModule is suitable for use in portable and embedded systems which have limited space and power consumption.

Unlike standard IDE drives, no signal cable and extra, special space is required. The DiskOnModule is a solid-state solution for IDE Hard Disk drive, which has no moving parts. That provides a good stability in a moving system. The DiskOnModule products are also free from extra and special algorithm or some firmware driver. Just plug the DiskOnModule into the IDE slot and play it, users can play the DiskOnModule as same as the Hard Disk Drives.

The DiskOnModule family provides the capacities ranging from 32MB up to 4GB. In the future, the capacity will be increased up to 8GB.



# 4. Specification

Environment Specifications	<u> </u>		
Temperature(Industrial)	Operating	0°C to +70°C	
Temperature(maastriar)	Non-Operating	-40°C to +85°C	
Temperature(Wide Temp)		-40°C to +85°C	
remperature(wide remp)	Operating Non-Operating		
Bullette and a state		-55°C to +95°C	
Relative Humidity		8% to 95% (with no condensation)	
Vibration	Operating	15G	
	Non-operating	15G	
Shock	Operating	1000G	
	Non-operating	1000G	
Configuration			
Capacity		32Mbytes to 2Gbytes	
Sector size		512Bytes	
System Performance			
Media transfer rate *note 1	Read	4.3 MB/sec	
	Write	3.3 MB/sec	
Interface burst transfer rate			
PIO mode 2		8.3 MB/sec (max)	
Reliability			
MTBF		2,000,000 hours	
ECC		1bit random correction	
		2bits detection per each 256bytes	
Power Requirement			
Voltage		DC+3.3V±5%	
		DC +5.0V±10%	
Power Consumption	1		
Read		30mA (typ.)	
Write		28mA (typ.)	
Stand by		3mA (typ.)	
Dimensions		<u>'</u>	
Height		33.0mm ± 0.3mm	
Width		51.20mm ± 0.2mm	
Thickness		8.0mm± 0.2mm	
		<u>I</u>	

Note1: There will be different figures shown in different platforms



## **Capacity Specifications**

Capacity	Cylinder	Head	Sector	Total sectors
32MB	500	8	16	64000
64MB	500	8	32	128000
128MB	500	16	32	256000
256MB	1000	16	32	512000
512MB	1015	16	63	1023120
1024MB	2031	16	63	2047248
2048MB	4063	16	63	4095504



# 5. Physical Outline DG0XXXX44XX0 (44 PIN)

